

Massey Ferguson®

2635 Tractor

SERVICE MANUAL 4283424M3

CONTENTS

INTRODUCTION AND SAFETY	01
MISCELLANEOUS DATA	02
TRACTOR IDENTIFICATION AND SPECIFICATIONS	03
SPLITTING THE TRACTOR	04
SHEET METAL	05
T SJ436 E DIESEL ENGINES	06
FRONT AXLE	07A
FRONT AXLE - 4 WHEEL DRIVE	07B
DUAL CLUTCH	08A
SPLIT TORQUE CLUTCH	08B
8 SPEED TRANSMISSION - DUAL CLUTCH	09A
8X8 SPEED SHUTTLE GEARBOX	09B
TRANSFER GEARBOX AND DRIVE SHAFT	09C
REAR AXLE AND OIL IMMersed BRAKES	10A
LIFT HYDRAULICS	11A
AUXILIARY HYDRAULICS	11B
LIVE POWER TAKE - OFF	12A
INDEPENDENT POWER TAKE - OFF	12B
HYDROSTATIC STEERING	13
GENERAL ELECTRICALS	14A
WHEELS AND TIRES	15A
DRAWBAR AND LINKAGES	16A
STORAGE CARE	17A

SECTION 2

Miscellaneous Data

SECTION 2

Miscellaneous Data

Operation NO	Description	Page No
2.1	Bolt Torque Specification for inch	2A - 3
2.2	Bolt Torque Specification for MM	2A - 4
2.3	Conversion tables	2A - 5

2.1 BOLT TORQUE SPECIFICATIONS (GENERAL GUIDE FOR INCH FASTENERS)

Use the "Standard Torque" charts as a general guide when tightening fasteners that DO NOT HAVE SPECIFIC TIGHTENING RECOMMENDATIONS.

Inch Fasteners					
Standard torque in Newton Metres (Foot pounds)					
*Inch bolt size	SAE grade 5 ** mild steel below grade 5	SAE grade 8 ISO grade 8.8 BS grade S		ISO grade 10.9 BS grade V	
		*** Non-rigid joint	**** Rigid joint	*** Non-rigid joint	**** Rigid joint
1/4 inch	6 - 8 (4 - 6)	9 - 12 (7 - 9)	11 - 15 (8 - 11)	13 - 18 (10 - 13)	16 - 22 (12 - 16)
5/16 inch	12 - 16 (9 - 12)	18 - 24 (13 - 18)	22 - 30 (16 - 22)	25 - 34 (18 - 25)	31 - 43 (23 - 32)
3/8 inch	22 - 30 (16 - 22)	31 - 42 (23 - 31)	39 - 53 (29 - 39)	44 - 60 (32 - 44)	55 - 75 (41 - 55)
7/16 inch	35 - 47 (26 - 35)	51 - 69 (38 - 51)	64 - 86 (47 - 63)	72 - 96 (53 - 71)	90 - 120 (66 - 89)
1/2 inch	54 - 72 (40 - 53)	80 - 104 (59 - 77)	100 - 130 (74 - 96)	110 - 140 (81 - 103)	140 - 180 (103 - 133)
5/8 inch	110 - 140 (81 - 103)	160 - 210 (118 - 155)	200 - 260 (148 - 192)	220 - 300 (162 - 221)	280 - 370 (207 - 273)
3/4 inch	190 - 250 (140 - 184)	280 - 370 (207 - 273)	350 - 460 (258 - 339)	390 - 530 (287 - 391)	490 - 660 (361 - 487)
7/8 inch	310 - 410 228 - 302	450 - 610 (332 - 450)	560 - 760 (413 - 561)	640 - 850 (472 - 672)	800 - 1060 (590 - 782)
1 inch	460 - 620 (339 - 457)	670 - 900 (494 - 664)	840 - 1120 (620 - 826)	960 - 1280 (708 - 944)	1200 - 1600 (885 - 1180)

Key to table above:

- * **NOTE:** The size is the diameter of the shank - not the head width.
- ** **NOTE:** Mild steel torque values to be used for SAE Grade 5 bolts when weld nuts, or other low strength nuts are used.
- *** **NOTE:** Use these values when any of the following conditions exist:
 1. Possible damage to the joined members of the assembly may occur.
 2. Thick and/or highly compressible gaskets are used between members.
 3. Non -flat unmachined seating surfaces for bolt head (or nut) occurs.
 4. Non -flat or non -parallel joint faces are encountered.
- **** **NOTE:** Use these values when ALL of the following conditions exist:
 1. Damage will not occur to the joined members of the assembly.
 2. It is desirable to use this higher clamping force to ensure tightness.
 3. Fastener thread is not lubricated prior to assembly.

2.2 BOLT TORQUE SPECIFICATIONS (GENERAL GUIDE FOR METRIC FASTENERS)

Use the "Standard Torque" charts as a general guide when tightening fasteners that DO NOT HAVE SPECIFIC TIGHTENING RECOMMENDATIONS

Inch Fasteners					
Standard torque in Newton Metres (Foot pounds)					
*Inch bolt size	SAE grade 5 ** mild steel below grade 5	SAE grade 8 ISO grade 8.8 BS grade S		ISO grade 10.9 BS grade V	
		*** Non-rigid joint	**** Rigid joint	*** Non-rigid joint	**** Rigid joint
M6	4 - 5 (3 - 4)	8 - 11 (6 - 8)	10 - 14 (7 - 10)	12 - 16 (9 - 12)	14 - 20 (10 - 15)
M8	10 - 13 (7 - 10)	20 - 28 (15 - 21)	25 - 35 (18 - 26)	29 - 37 (21 - 27)	36 - 46 (27 - 34)
M10	19 - 25 (14 - 18)	40 - 56 (30 - 41)	50 - 70 (37 - 52)	57 - 77 (42 - 57)	72 - 96 (53 - 71)
M12	33 - 43 (24 - 32)	72 - 96 (53 - 71)	90 - 120 (66 - 89)	100 - 130 (74 - 96)	120 - 160 (89 - 118)
M16	84 - 110 (62 - 81)	160 - 210 (118 - 155)	200 - 260 (148 - 192)	240 - 320 (177 - 236)	300 - 400 (221 - 295)
M20	160 - 210 (118 - 115)	340 - 450 (251 - 332)	420 - 560 (310 - 413)	480 - 640 (354 - 472)	600 - 800 (443 - 590)

Key to table above:

- * *NOTE: The size is the diameter of the shank - not the head width.*
- ** *NOTE: Mild steel torque values to be used for SAE Grade 5 bolts when weld nuts, or other low strength nuts are used.*
- *** *NOTE: Use these values when any of the following conditions exist:*
 1. Possible damage to the joined members of the assembly may occur.
 2. Thick and/or highly compressible gaskets are used between members.
 3. Non -flat unmachined seating surfaces for bolt head (or nut) occurs.
 4. Non -flat or non -parallel joint faces are encountered.
- **** *NOTE: Use these values when ALL of the following conditions exist:*
 1. Damage will not occur to the joined members of the assembly.
 2. It is desirable to use this higher clamping force to ensure tightness.
 3. Fastener thread is not lubricated prior to assembly.

2.3 CONVERSION TABLES

Area	Multiply by	Pressure	Multiply by
mm ² to in ²	0.0015	bar to lbf/in ²	14.504
in ² to mm ²	645.16	lbf/in ² to bar	0.0690
m ² to ft ²	10.764		
ft ² to m ²	0.0929	Speed	Multiply by
ha to acre	2.4711	km/hr to mile/hr	0.6214
acre to ha	0.4047	mile/hr to km/hr	1.6093
Capacity	Multiply by	Torque	Multiply by
ml to fluid oz	0.0351	Nm to lbf ft	0.738
fluid oz to ml	28.413	lbf ft to Nm	1.356
litre to gal	0.2200		
gal to litre	4.5640	Volume	Multiply by
litre to US gal	0.2640	mm ³ to in ³	0.6102
US gal to litre	3.7850	in ³ to mm ³	163.87
gal to US gal	1.2010	m ³ to ft ³	35.315
US gal to gal	0.8330	ft ³ to m ³	0.0283
Length	Multiply by	Weight	Multiply by
mm to in	0.0394	gram to oz	0.3530
in to mm	25.400	oz to gram	28.350
m to ft	3.2808	kg to lb	2.2046
ft to m	0.3048	lb to kg	0.4536
km to mile	0.6214	kg to ton	0.0010
mile to km	1.6093	ton to kg	1016.1
tonne to ton	0.9842		
ton to tonne	1.0160		
Power	Multiply by	Temperature	
ps to hp	0.9863	°C to °F $1.8 \times ^\circ\text{C} + 32$	
hp to ps	1.0139	°F to °C $(^\circ\text{F} - 32) \div 1.8$	
kW to hp	1.3410		
hp to kW	0.7457		

PAGE LEFT BLANK INTENTIONALLY